



## CT440 Compact Tractor



***One Tough Animal™***

## Specifications

<b>Model</b>	<b>CT440</b>
<b>Engine</b>	Diesel - Interim Tier IV
Gross Power	41 hp (30.6 kW)
No. of Cylinders	4
Total Displacement	2.0 L (122 cu. in.)
Fuel Tank Capacity	45.0 L (11.9 gal.)
<b>3-PT, PTO, &amp; Hydraulics</b>	
PTO Horsepower	22.3 kW (30 hp)
Three-Point Hitch	Category I
Lift Control Type	Hydraulic Position Control System
Lift Capacity at 24 in. behind lift point (per SAE J283)	848 kg (1870 lb.)
Maximum hydraulic lift capacity at 24 in. behind lift points (measured at 15 in. above ground)*	1190 kg (2625 lb.)
Rear PTO	540 rpm
Rear PTO System	Independent
Mid-PTO (optional)	2000 rpm
Total Hydraulic Pump Capacity	61.0 L/min. (16.1 gpm)
Implement	36.0 L/min. (9.5 gpm)
Steering	25.0 L/min. (6.6 gpm)
Rear Hydraulics (optional)	Single or Dual
Telescopic Stabilizers	Standard
Lower Links	Telescopic
Lifting Rod	Crank
<b>Drive System</b>	
Transmission	Hydrostatic
Speed Ranges	3
Brakes	Wet Disc
Rear Diff. Lock	Std
Four Wheel Drive	Std
<b>Travel Speeds (w/ Ag Tires)</b>	
Range 1 (low)	6.3 km/hr (0 - 3.9 mph)
Range 2 (med)	10.8 km/hr (0 - 6.8 mph)
Range 3 (high)	26.5 km/hr (0 - 16.7 mph)
Reverse	17.8 km/hr (0 - 11.2 mph)
<b>Dimensions</b>	
Overall Length (w/ 3-PT)	3411 mm (134.3 in.)
Overall Width (w/ Ag Tires)	1753 mm (69 in.)
Overall Height (w/ ROPS up)	2426 mm (95.5 in.)
Wheelbase	1875 mm (73.8 in.)
Ground Clearance	356 mm (14 in.)
Operating Weight	1745 kg (3847 lb.)
<b>Steering</b>	Hydrostatic Power Steering
Inside Turning Radius	3353 mm (132 in.)
Tilt Steering Wheel	Std
<b>Tire Sizes</b>	
General Purpose- Front/Rear	10x16.5 6PR / 14.9x24 8PR
Turf- Front/Rear	29x12.5-15 8PR / 21.5Lx16.1 4PR
Ag- Front/Rear	8x16 10PR / 13.6x24 6PR
<b>Safety Equipment</b>	
Safety Interlock System (neutral start-operating)	Std
Fold Down ROPS (roll-over protective structure)	Std
Fully Retractable Seat Belt	Std
<b>Features</b>	
Suspension Seat	Std
Cup Holder	Std
Glow Plug Engine Preheat	Std
Toolbox	Std
Head Lights/Tail Lights/Brake Lights	Std
Cruise Control	Std
Spark Arrestor Muffler	Std
Horn/Hazard Flasher/Turn Signals	Std
<b>Attachments</b>	
Loader Rated Capacity @ 500 mm in front of bucket pin (w/Rear Ballast)	929 kg (2050 lb.)
Loader Lift Capacity @ Bucket Pivot (w/Rear Ballast)	1179 kg (2600 lb.)
Bucket Widths	54 in., 60 in., 68 in., 72 in.
Loader Max Lift Height @ Bucket Pivot	2847 mm (112.1 in.)
<b>Accessories</b>	
Rear Working Lights	Opt
Side Mirror	Opt
Sunshade	Opt
Grill Guard	Opt
Slow Moving Vehicle Emblem	Opt

\*Note: Hydraulic 3-pt. lift capacity will vary depending on lift point height.

## THE GOOD LIFE BEGINS AT 440

Whether it's keeping your home acreage maintained or working on a tough landscaping or grounds maintenance project, the CT440's 41 horsepower engine and smooth, comfortable operation makes life easier on the job. Its added power and premium features come in handy working in tough terrain, and it can efficiently pull or power a variety of implements.

### Premium 3-Point Hitch for fast, easy implement changes

- Easily move the links from side to side or up and down with telescoping sway bars and lower links, plus crank style lower link adjustment
- Rear remote 3-point position control lever allows you to quickly raise and lower 3-point lower links from the rear of the tractor
- Independent PTO comes standard. Just flip a switch to engage, or disengage, the PTO without stopping or using a clutch

### Outstanding Performance

- Rear remote 3-point position control lever allows you to quickly raise and lower 3-point lower links from the rear of the tractor
- Independent PTO comes standard. Just flip a switch to engage, or disengage, the PTO without stopping or using a clutch

### Superior Comfort and Visibility

- Hydrostatic transmission with three travel speed ranges for easy operation
- Sleek hood and side panels are made of tough, durable steel, not plastic, and provide great visibility
- Exclusive Bobcat suspension seat for extended comfort
- Fully retractable seat belt within easy reach
- Optional ROPS Cab

Bobcat CT440: get a lot of tractor and get it done.

NOTE - Where applicable, dimensions are in accordance with Society of Automotive Engineers (SAE) and ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for loader equipped with standard tires. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.



Easy Maintenance

## Bobcat Implements:

- 3 pt. Angle Blade
- 3 pt. Auger
- 3 pt. Box Blade
- 3 pt. Finish Mower
- 3 pt. Rotary Cutter
- 3 pt. Snowblower
- 3 pt. Soil Cultivator
- 3 pt. Tiller
- 3 pt. Tine Rake
- Backhoe
- Front-End Loader