



CT445 Compact Tractor



One Tough Animal

Specifications

Model	CT445
Engine	Diesel - Interim Tier IV
Gross Power	33.6 kW (45 hp)
No. of Cylinders	4
Total Displacement	2.2 L (134.3 cu. in.)
Fuel Tank Capacity	45.0 L (11.9 gal)
3-PT, PTO, & Hydraulics	
PTO Horsepower	25.4 kW (34 hp)
Three-Point Hitch	Category I
Lift Control Type	Hydraulic Position Control System
Lift Capacity at 24 in. behind lift point (per SAE J283)	848 kg (1870 lb.)
Maximum hydraulic lift capacity at 24 in. behind lift points (measured at 15 in. above ground)*	1190 kg (2625 lb.)
Rear PTO	540 rpm
Rear PTO System	Independent
Mid-PTO (optional)	2000 rpm
Total Hydraulic Pump Capacity	61.0 L/min. (16.1 gpm)
Implement	36.0 L/min. (9.5 gpm)
Steering	25.0 l/min. (6.6 gpm)
Rear Hydraulics (optional)	Single or Dual
Telescopic Stabilizers	Standard
Lower Links	Telescopic
Lifting Rod	Crank
Drive System	
Transmission	Hydrostatic
Speed Ranges	3
Brakes	Wet Disc
Rear Diff. Lock	Std
Four Wheel Drive	Std
Travel Speeds (w/ Ag Tires)	
Range 1 (low)	6.3 km/hr (0 - 3.9 mph)
Range 2 (med)	10.8 km/hr (0 - 6.7 mph)
Range 3 (high)	26.5 km/hr (0 - 16.7 mph)
Reverse	17.8 km/hr (0 - 11.2 mph)
Dimensions	
Overall Length (w/ 3-PT)	3411 mm (134.3 in.)
Overall Width (w/ Ag Tires)	1753 mm (69 in.)
Overall Height (w/ ROPS up)	2426 mm (95.5 in.)
Wheelbase	1875 mm (73.8 in.)
Ground Clearance	356 mm (14 in.)
Operating Weight	1760 kg (3881 lb.)
Steering	
Inside Turning Radius	Hydrostatic Power Steering
Tilt Steering Wheel	3353 mm (132 in.)
	Std
Tire Sizes	
General Purpose- Front/Rear	10x16.5 6PR / 14.9x24 8PR
Turf- Front/Rear	29x12.5-15 8PR / 21.5Lx16.1 4PR
Ag- Front/Rear	8x16 10PR / 13.6x24 6PR
Safety Equipment	
Safety Interlock System (neutral start-operating)	Std
Fold Down ROPS (roll-over protective structure)	Std
Fully Retractable Seat Belt	Std
Features	
Suspension Seat	Std
Cup Holder	Std
Glow Plug Engine Preheat	Std
Toolbox	Std
Head Lights/Tail Lights/Brake Lights	Std
Cruise Control	Std
Spark Arrestor Muffler	Std
Horn/Hazard Flasher/Turn Signals	Std
Attachments	
Loader Rated Capacity @ 500 mm in front of bucket pin (w/Rear Ballast)	929 kg (2050 lb.)
Loader Lift Capacity @ Bucket Pivot (w/Rear Ballast)	1179kg (2600 lb.)
Bucket Widths	54 in., 60in., 68 in., 72 in.
Loader Max Lift Height @ Bucket Pivot	2847 mm (112.1 in.)
Accessories	
Rear Working Lights	Opt
Side Mirror	Opt
Sunshade	Opt
Grill Guard	Opt
Slow Moving Vehicle Emblem	Opt

*Note: Hydraulic 3-pt. lift capacity will vary depending on lift point height.

LINK UP TO EXTRA POWER

Whether you're navigating hills or powering through your toughest jobs, the Bobcat CT445 is ready to work. With a 45 horsepower engine, you'll have extra muscle to do the job faster. Add its premium 3-point hitch and simple, ergonomic controls, plus a wide variety of implements, and there's no stopping you.

Premium 3-Point Hitch for fast, easy implement changes

- Easily move the links from side to side or up and down with telescoping sway bars and lower links, plus crank style lower link adjustment
- Rear remote 3-point position control lever allows you to quickly raise and lower 3-point lower links from the rear of the tractor
- Independent PTO comes standard. Just flip a switch to engage, or disengage, the PTO without stopping or using a clutch

Outstanding Performance

- Steering brakes to tighten your turning radius in tight spaces
- Standard 4WD for working in tough conditions
- Beefy construction for added weight, more power to the ground

Superior Comfort and Visibility

- Hydrostatic transmission with three travel speed ranges for easy operation
- Sleek hood and side panels are made of tough, durable steel, not plastic, and provide great visibility
- Exclusive Bobcat suspension seat for extended comfort
- Fully retractable seat belt within easy reach
- Optional ROPS Cab

Bobcat CT445: power up your productivity.

NOTE - Where applicable, dimensions are in accordance with Society of Automotive Engineers (SAE) and ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for loader equipped with standard tires. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.



Easy Maintenance

Bobcat Implements:

- 3 pt. Angle Blade
- 3 pt. Auger
- 3 pt. Box Blade
- 3 pt. Finish Mower
- 3 pt. Rotary Cutter
- 3 pt. Snowblower
- 3 pt. Soil Cultivator
- 3 pt. Tiller
- 3 pt. Tine Rake
- Backhoe
- Front-End Loader

Bobcat Company
P.O. Box 6000 • West Fargo, ND 58078
www.bobcat.com

