



## CT450 Compact Tractor



***One Tough Animal***

## Specifications

<b>Model</b>	<b>CT450</b>
<b>Engine</b>	Diesel - Interim Tier IV 37.3 kW (50 hp) 4 2.4 L (146.5 cu. in.) 45.0 L (11.9 gal)
<b>3-PT, PTO, &amp; Hydraulics</b>	28.3 kW (38 hp) Category I Hydraulic Position Control System 848 kg (1870 lb.) 1190 kg (2625 lb.) 540 rpm Independent 2000 rpm 61.0 L/min. (16.1 gpm) 36.0 L/min. (9.5 gpm) 25.0 l/min. (6.6 gpm) Single or Dual Standard Telescopic Crank
<b>Drive System</b>	Hydrostatic 3 Wet Disc Std Std
<b>Travel Speeds (w/ Ag Tires)</b>	6.3 km/hr (0 - 3.9 mph) 10.8 km/hr (0 - 6.7 mph) 26.5 km/hr (0 - 16.7 mph) 17.8 km/hr (0 - 11.2 mph)
<b>Dimensions</b>	3411 mm (134.3 in.) 1753 mm (69 in.) 2426 mm (95.5 in.) 1875 mm (73.8 in.) 356 mm (14 in.) 1785 kg (3935 lb.)
<b>Steering</b>	Hydrostatic Power Steering 3353 mm (132 in.) Std
<b>Tire Sizes</b>	General Purpose- Front/Rear Turf- Front/Rear Ag- Front/Rear 10x16.5 6PR / 14.9x24 8PR 29x12.5-15 8PR / 21.5Lx16.1 4PR 8x16 10PR / 13.6x24 6PR
<b>Safety Equipment</b>	Safety Interlock System (neutral start-operating) Std Fold Down ROPS (roll-over protective structure) Std Fully Retractable Seat Belt Std
<b>Features</b>	Suspension Seat Cup Holder Glow Plug Engine Preheat Toolbox Head Lights/Tail Lights/Brake Lights Cruise Control Spark Arrestor Muffler Horn/Hazard Flasher/Turn Signals Std Std Std Std Std Std Std
<b>Attachments</b>	Loader Rated Capacity @ 500 mm in front of bucket pin (w/Rear Ballast) 929 kg (2050 lb.) Loader Lift Capacity @ Bucket Pivot (w/Rear Ballast) 1179kg (2600 lb.) Bucket Widths 54 in., 60in., 68 in., 72 in. Loader Max Lift Height @ Bucket Pivot 2847 mm (112.1 in.)
<b>Accessories</b>	Rear Working Lights Side Mirror Sunshade Grill Guard Slow Moving Vehicle Emblem Opt Opt Opt Opt Opt

\*Note: Hydraulic 3-pt. lift capacity will vary depending on lift point height.

## COMMAND THE LAND

With its 50 horsepower engine and premium 3-point hitch, the CT450 is fully equipped for a wide variety of heavy-duty chores and grounds maintenance jobs. The easy operation, extended comfort and great implement performance will help you do more, do it faster and do it better.

### Premium 3-Point Hitch for fast, easy implement changes

- Easily move the links from side to side or up and down with telescoping sway bars and lower links, plus crank style lower link adjustment
- Rear remote 3-point position control lever allows you to quickly raise and lower 3-point lower links from the rear of the tractor
- Independent PTO comes standard. Just flip a switch to engage, or disengage, the PTO without stopping or using a clutch

### Outstanding Performance

- Steering brakes to tighten your turning radius in tight spaces
- Standard 4WD for working in tough conditions
- Beefy construction for added weight, more power to the ground

### Superior Comfort and Visibility

- Hydrostatic transmission with three travel speed ranges for easy operation
- Sleek hood and side panels are made of tough, durable steel, not plastic, and provide great visibility
- Exclusive Bobcat suspension seat for extended comfort
- Fully retractable seat belt within easy reach
- Optional ROPS Cab

Bobcat CT450 – the ultimate in performance and productivity!

NOTE - Where applicable, dimensions are in accordance with Society of Automotive Engineers (SAE) and ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for loader equipped with standard tires. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.



Easy Maintenance

## Bobcat Implements:

- 3 pt. Angle Blade
- 3 pt. Auger
- 3 pt. Box Blade
- 3 pt. Finish Mower
- 3 pt. Rotary Cutter
- 3 pt. Snowblower
- 3 pt. Soil Cultivator
- 3 pt. Tiller
- 3 pt. Tine Rake
- Backhoe
- Front-End Loader